



**SNAPSPORTS<sup>®</sup>**  
ATHLETIC SURFACES

# **MAINTENANCE MANUAL & PRODUCT GUIDE**

***FOR ALL SNAPSPORTS LIGHT & DARK  
MAPLE VINYL (12", 18", 36") PRODUCTS***

## Overview

SnapSports floors should be kept as clean as possible. Daily cleaning with a dust mop or the like is highly recommended. Grit from dust and dirt will cause micro-abrasions on the flooring that tend to dull the surface and make it harder to keep clean.

## Floor Care Maintenance Program

### MAINTENANCE PRODUCTS:

#### Removable Topical Coating

**CENTI Finish** is an environmentally preferred acrylic floor finish. This low odor finish has exceptional performance properties and can be maintained with conventional procedures. CENTI Finish contains no zinc or other heavy metals that can be harmful to wastewater treatment systems.

#### Daily Cleaner

**CENTI Cleaner** is a super-concentrated no-rinse floor cleaner formulated with biodegradable surface-active agents. CENTI Cleaner removes surface dirt without diminishing the shine. CENTI Cleaner lifts and neutralizes haze left by chemical ice melt products. Use daily at 2 oz./gallon. CENTI Cleaner can be mopped on or used in automatic scrubbers. It is neutral pH so it will not dull or strip any finish, and has a pleasant floral fragrance.

#### Daily Maintainer/Cleaner

**CENTI Maintainer** is a cleaner / maintainer for automatic scrubber or mop-on use. Floors maintained with CENTI Maintainer require less re-coating with floor finish. CENTI Maintainer repairs scuffing and scratching while leaving a micro layer that dries to a gloss appearance. Highly economical - use only 2 oz. per gallon for daily maintenance. CENTI Maintainer is formulated with biodegradable surface active agents.

#### Periodic Finish Stripper

**CENTI Strip** is a super concentrated floor finish stripper. CENTI Strip is fast penetrating and simple to use. CENTI Strip has been designed to be especially effective on today's Green finishes. Has a low odor, non-rinse, non-butyl formula.

#### Oil Flo Black Mark Remover

**Oil Flo** is a cleaner to remove deep scuff marks from the maple surface. Oil Flo is fast penetrating and simple to use.

## Directions for Use

### DAILY MAINTENANCE

#### Equipment:

Mop bucket or automatic floor scrubber

#### Cleaning Products:

CENTI Maintainer

#### Directions:

Clean all surfaces with dust mop. Mix a solution of CENTI Maintainer with water in mop bucket or solution tank of automatic scrubber, at a dilution rate of 2 oz. per gallon of water. Mix thoroughly. Apply solution per your chosen application method and allow to dry fully. For deep black marks use the Oil Flo Black Mark Remover and a tennis ball on a stick or a red scrubber pad.

**WEEKLY MAINTENANCE****Equipment:**

Mop bucket, Mop & 175–200 RPM buffer

*Optional: Auto scrubber with red pad*

**Cleaning Products:**

CENTI Cleaner

**Directions:**

Clean all surfaces with dust mop. Mix a solution of CENTI Maintainer with water in mop bucket or solution tank of automatic scrubber, at a dilution rate of 2 oz. per gallon of water. Mix thoroughly. Apply solution per your chosen application method and allow to dry fully. For deep black marks use the Oil Flo Black Mark Remover and a tennis ball on a stick or a red scrubber pad.

**COMPLETE SURFACE CLEAN / STRIP****Equipment:**

Mop bucket, Mop & 175–200 RPM buffer

*Optional: Auto scrubber with red pad*

**Cleaning Products:**

CENTI Strip

**Directions:**

Clean all surfaces with dust mop. Mix a solution of CENTI Strip with water in mop bucket or solution tank of automatic scrubber, at a dilution rate of 2 oz. per gallon of water. Mix thoroughly. Apply solution per your chosen application method. Agitate area with buffer until product foams and cleans surface. Wet vacuum or mop to remove residue. Allow to dry. You can also use an auto scrubber for larger applications.

**ACRYLIC MAINTENANCE COATING APPLICATION**

Recommended for all Maple vinyl products where a protective maintenance finish is desired.

**Equipment:**

Mop bucket, Mop & 175–200 RPM buffer

*Optional: Auto scrubber with red pad*

**Cleaning Products:**

CENTI Strip

**Directions:**

Clean all surfaces with CENTI Cleaner all-purpose cleaner. Allow floor to dry fully. For smaller areas, apply a thin coat of Restore with a microfiber or similar mop. When dry, apply a second as before, but try to apply at a 90 degree angle to the first application. Apply additional coats, if needed in the same manner.

For larger areas, the process works best with two people. Get a small (1–2 gallon) poly garden sprayer from a hardware store. Also get a small, rectangular headed mop with a long handle. While the first person sprays a fine mist of Restore in a manageable area, the second person uses the mop to apply a smooth consistent coating. When dry, apply a second as before, but try to apply at a 90 degree angle to the first application. Apply additional coats, if needed in the same manner.

**COMPLETE SURFACE RESTORATION****Equipment:**

Mop bucket, Mop & 175–200 RPM buffer

*Optional: Auto scrubber with red pad*

**Cleaning Products:**

CENTI Strip; CENTI Finish

**Directions:**

Clean all surfaces with dust mop. Mix a solution of CENTI Strip with water in mop bucket or solution tank of automatic scrubber, at a dilution rate of 2 oz. per gallon of water. Mix thoroughly. Apply solution per your chosen application method. Agitate area with buffer until product foams and cleans surface. Wet vacuum or mop to remove residue. Allow to dry. You can also use an auto scrubber for larger applications. Do not start the next step until floor is completely dry.

For smaller areas, apply a thin coat of CENTI Finish with a microfiber or similar mop. When dry, apply a second as before, but try to apply at a 90 degree angle to the first application. Apply additional coats, if needed in the same manner.

For larger areas, the process works best with two people. Get a small (1–2 gallon) poly garden sprayer from a hardware store. Also get a small, rectangular headed mop with a long handle. While the first person sprays a fine mist of CENTI Finish in a manageable area, the second person uses the mop to apply a smooth consistent coating. When dry, apply a second as before, but try to apply at a 90 degree angle to the first application. Apply additional coats, if needed in the same manner.

**ANTI-STATIC****Equipment:**

Mop bucket & Mop

*Optional: Sprayer*

**Cleaning Products:**

Anti-Static

**Directions:**

Dilute anti-static liquid 1:4 in water (1 part anti-static, 4 parts water) or per directions. Apply light coat to surface with either mop or with sprayer/mop combination. Do not allow solution to puddle. Allow to dry.

